



- An architectural, square, IP65, ultra shallow LED solution.

- Semi-Recessed; ideal for restricted voids

- Available in 8W (100mm), 11W (125mm), 15W (155mm), 22W (185mm) & 30W (215mm)
 - Square: 556/855/1066/1507/2347 lumens
 - Shallow Depth: 20mm (depth without driver, driver depth may vary)
 - Available with Dimming (/STD/DALI/SDIM/MDIM)
 - Colour Temperatures: 3000k - 4000k - 6500k
 - Bezel Options: White (/WH)
- Available with remote Emergency (/RME3/RME3-ST/RME3-PRO)

Product	MIR/WAF-P/SQ Semi-Recessed WAFER-P Square				
Lamp	LED				
Lamp Power <small>Luminaire lumens (4000K)</small>	/8W 556lm	/11W 855lm	/15W 1066lm	/22W 1507lm	/30W 2347lm
Size Cut-out	100 x 100mm Ø 80mm	125 x 125mm Ø 105mm	155 x 155mm Ø 135mm	185 x 185mm Ø 165mm	215 x 215mm Ø 195mm
Driver	/STD Non Dimming	/DALI DALI Dimming		/SDIM Switch Dimming	/MDIM Mains Dimming
Colour Temperature	/830 3000k		/840 4000k		/865 6500k
Bezel Colour	/WH White				
Diffuser Options	/OP Opal Diffuser				
Emergency	/RME3 Remote Three hour maintained emergency		/RME3-ST Remote three hour maintained self test emergency		/RME3-PRO Remote Three hour DALI addressable emergency
To Specify: WAFER-P SQUARE LED, 15W, 4000k, 1066lm LED semi-recessed downlight finished white supplied complete with remote control gear. Part code: MIR/WAF-P/SQ/15W/1066lm/STD/840/WH/OP					

