



**A cast aluminium LED IP65 amenity exterior luminaire available with various diffuser options.**

- A lumen output of 3114lm
- Colour Temperature: 4000k - 5000k
- Colour: Black(/BK)
- Available with Dimming (/STD/1-10V)
- Emergency Options(/ME3/ME3-ST/ME3-PRO)
- Wireless Control (/WI)
- Wireless Emergency (/ME3-WI)
- Mountings: Surface mounted
- Diffuser options: Polycarbonate reeded diffuser (/RD)
- Sensor: Daylight photocell option (/PC)
- IP Rating: IP65
- Housing: Die cast aluminium body
- Dimensions: (Length x Width x Depth)  
299 x 267 x 184mm

Product	MI/WM Bulkhead IP65 LED Luminaire			
Light Source	LED			
System Power <small>Luminaire lumens (5000K)</small>	/36.6W 3114lm			
Size	299 x 267 x 184mm			
Driver	/STD Non Dimming		/1-10V 1-10V Dimming	
Colour Temperature	/840 4000k		/850 5000k	
Colour	/BK Black			
Diffuser Options	/RD Reeded diffuser			
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour main- tained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emergency
To Specify: WALLMATE LED, 36.6W, 3114lm, 5000k, Reeded Diffuser LED surface mounted finished black complete with stand- ard control gear. Part code: MI/WM/LED/36.6W/3114lm/STD/850/RD/BK				

