



**- A high quality cornice LED luminaire ideally suited for circulation areas.**

- A range of lumen outputs from 3010-6390lm
- Colour Temperatures: 3000k - 4000k - 5000k
  - Rated IP44
  - Extruded aluminium body
  - Available with tamper proof screws
  - Available with Dimming (/STD/DALI/SDIM)
- Available with Emergency (/ME3/ME3-ST//ME3-PRO)
- Dimensions: 300/600/1200/1500 x 121 x 63mm

Product	MIS/APEX Surface LED cornice luminaire		
Lamp	LED		
Lamp Power Luminaire lumens (4000K)	/27W 3010lm	/34W 3750lm	/58W 6390lm
Size	/3 300mm	/6 600mm	/12 1200mm
Driver	/STD Non Dimming	/DALI DALI Dimming	
Colour Temperature	/830 3000k	/840 4000k	/850 5000k
Colour	/WH White		
Diffuser Options	/OP Opal Diffuser		
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency
To Specify: APEX LED, 34W, 3750lm, 4000k, LED surface cornice finished white supplied complete with DALI control gear and opal diffuser. Part code: MIS/APEX/LED/34W/3750lm/12/DALI/840/WH/OP			

